

# DECLARATION OF PERFORMANCE

DOP: LWHW1042020

1. Unique identification code of the product type:

EN 13984 Type A-Regenerated Damp-Proof Membrane 100

2. Intended use:

Plastic sealing sheet without reinforcement for use as a damp-proof membrane in construction

3. Manufacturer:

Kronoflooring GmbH, Mühlbacher Strasse 1, 01561 Lampertswalde, Germany

4. Authorized representative:

Not applicable

5. System(s) of assessment and verification of constancy of performance (AVCP):

System 3

6. a) Harmonized standard:

EN 13984

6. b) Notified body (bodies):

Materials Testing Agency North Rhine-Westphalia  
Marsbruchstr. 186  
44287 Dortmund  
Notified body no. 0432

7. Declared performance(s):

Essential characteristics	Performance	Harmonized techn. specification
Watertightness	passed	EN 1928
Resistance to impact load	<200 mm	EN 12691
Water vapor permeability resistance following artificial aging	passed	EN 1296
Resistance to chemicals	passed	EN 12311-2
Shear resistance of joining seams	KLF/NPD	EN 12317-2
Water vapor permeability resistance	>100m	EN ISO 1931
Tensile strength, lengthwise	>67 N/50mm	EN 12311-2
Tensile strength, crosswise	>67 N/50mm	EN 12311-2
Tear propagation force, lengthwise	> 90 N	EN 12310-1
Tear propagation force, crosswise	> 80 N	EN 12310-1
Expansion lengthwise	>350 %	EN 12311-2
Expansion, crosswise	>450 %	EN 12311-2
Fire performance	Class E	EN 13501-1
Hazardous substances	Not relevant	

8. Appropriate technical documentation and/or Specific Technical Documentation:

Not applicable

The performance of the above product corresponds to the declared performance/declared performances. The above-named manufacturer is solely responsible for drawing up the Declaration of Performance in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

Markus Oberbauer, Managing Director

(Name and position)

Lampertswalde, 23.08.2021

(Date and place)



(Signature)

english